

由于工作的关系，我已经有将近半年时间没去动过 asp 的东东了，不过一些资料还保留在机器上，ASP 函数在实际程序中的运用很实际，能解决你很多问题，我把我自己收藏的一些，还有自己写的一些函数给弄出来，希望能对大家有用:)



### 1.判断文件名是否合法

```
<%  
Function isFilename(aFilename)  
Dim sErrorStr,iNameLength,i  
isFilename=TRUE  
sErrorStr=Array("/","\",":","*","?","\"","<",">","|")  
iNameLength=Len(aFilename)  
If iNameLength<1 Or iNameLength=null Then  
isFilename=FALSE  
Else  
For i=0 To 8  
If instr(aFilename,sErrorStr(i)) Then  
isFilename=FALSE  
End If  
Next  
End If  
End Function  
>%
```

### 2.去掉字符串头尾的连续的回车和空格

```
<%  
function rtrimVBcrLf(str)  
dim pos,isBlankChar  
pos=len(str)  
isBlankChar=true  
while isBlankChar and pos>=2  
if mid(str,pos,1)=" " then  
pos=pos-1  
elseif mid(str,pos-1,2)=VBcrLf then  
pos=pos-2  
else  
isBlankChar=false  
end if  
wend  
rtrimVBcrLf=rtrim(left(str,pos))  
end function  
>%
```



### 3.去掉字符串开头的连续的回车和空格



```
<%  
function ltrimVBcrLf(str)  
    dim pos,isBlankChar  
    pos=1  
    isBlankChar=true  
    while isBlankChar  
        if mid(str,pos,1)=" " then  
            pos=pos+1  
        elseif mid(str,pos,2)=VBcrLf then  
            pos=pos+2  
        else  
            isBlankChar=false  
        end if  
    wend  
    ltrimVBcrLf=right(str,len(str)-pos+1)  
end function  
>%
```



4.判断 Email 是否有效,返回 1 表示正确

```
<%  
Function isEmail(aEmail)  
    Dim iLocat,v,iLength,i,checkletter  
    If instr(aEmail,"@") = 0 Or instr(aEmail,".") = 0 Then  
        isEmail=0  
        EXIT FUNCTION  
    End If  
    iLocat=instr(aEmail,"@")  
    If instr(iLocat,aEmail,".")=0 Or instr(iLocat+1,aEmail,"@")>0 Then  
        isEmail=0  
        EXIT FUNCTION  
    End If  
    If left(aEmail,1)="." Or right(aEmail,1)="." Or left(aEmail,1)="@" Or right(aEmail,1)="@" Then  
        isEmail=0  
        EXIT FUNCTION  
    End If  
    v="1234567890abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ_-.@"  
    iLength=len(aEmail)  
    For i=1 To iLength  
        checkletter=mid(aEmail,i,1)  
        If instr(v,checkletter)=0 Then  
            isEmail=0  
            EXIT FUNCTION  
        End If  
    Next
```





```
isEmail=1  
End Function  
%>
```

#### 5.用 HTML 格式显示文本

```
<%  
function HTMLEncode(fString)  
if not isnull(fString) then  
    fString = replace(fString, ">", "&gt;")  
    fString = replace(fString, "<", "&lt;")  
  
    fString = Replace(fString, CHR(32), "&nbsp;")  
    fString = Replace(fString, CHR(34), "&quot;")  
    fString = Replace(fString, CHR(39), "&#39;")  
    fString = Replace(fString, CHR(13), "")  
    fString = Replace(fString, CHR(10) & CHR(10), "</P><P> ")  
    fString = Replace(fString, CHR(10), "<BR> ")  
    HTMLEncode = fString  
end if  
end function  
%>
```



#### 6.检查邮件

```
<%  
Function CheckEmail(strEmail)  
    Dim re  
    Set re = New RegExp  
    re.Pattern = "^[\w-\.\_]{1,}\@([\da-zA-Z]{1,}\.){1,}[\da-zA-Z]{2,3}$"  
    re.IgnoreCase = True  
    CheckEmail = re.Test(strEmail)  
End Function  
%>
```



#### 7.检查无效字符

```
<%  
Function CheckStr(ByVal ChkStr)  
    Dim Str:Str=ChkStr  
    Str=Trim(Str)  
    If IsNull(Str) Then  
        CheckStr = ""  
        Exit Function  
    End If  
    Dim re  
    Set re=new RegExp
```







### 9.脏字过滤功能

```
<%  
Function DelDirty(str)  
str=replace(str,"妈的","MD")  
str=replace(str,"靠","KAO")  
DelDirty=str  
End Function  
>
```

### 10.获取 IP 地址

```
<%  
Function Userip()  
    Dim GetClientIP  
    '如果客户端用了代理服务器，则应该用 ServerVariables("HTTP_X_FORWARDED_FOR")方法  
    GetClientIP = Request.ServerVariables("HTTP_X_FORWARDED_FOR")  
    If GetClientIP = "" or isnull(GetClientIP) or isempty(GetClientIP) Then  
        '如果客户端没用代理，应该用 Request.ServerVariables("REMOTE_ADDR")方法  
        GetClientIP = Request.ServerVariables("REMOTE_ADDR")  
    end if  
    Userip = GetClientIP  
End function  
>
```



### 11.判断数字是否整形

```
<%  
function isInteger(para)  
on error resume next  
dim str  
dim l,i  
if isNull(para) then  
isInteger=false  
exit function  
end if  
str=cstr(para)  
if trim(str)="" then  
isInteger=false  
exit function  
end if  
l=len(str)  
for i=1 to l
```



```
if mid(str,i,1)>"9" or mid(str,i,1)<"0" then
isInteger=false
exit function
end if
next
isInteger=true
if err.number<>0 then err.clear
end function
%>
```



## 12.得到浏览器目前的 URL

```
<%
Function GetCurURL()
  If Request.ServerVariables("HTTPS") = "on" Then
    GetCurrentURL = "https://"
  Else
    GetCurrentURL = "http://"
  End If
  GetCurURL = GetCurURL & Request.ServerVariables("SERVER_NAME")
  If (Request.ServerVariables("SERVER_PORT") <> 80) Then GetCurURL = GetCurURL & ":" & Request
.ServerVariables("SERVER_PORT")
  GetCurURL = GetCurURL & Request.ServerVariables("URL")
  If (Request.QueryString <> "") Then GetCurURL = GetCurURL & "?" & Request.QueryString
End Function
%>
```

## 13.测试变量是否为空值

```
<%
Function IsBlank(ByRef Var)
  IsBlank = False
  Select Case True
    Case IsObject(Var)
      If Var Is Nothing Then IsBlank = True
    Case IsEmpty(Var), IsNull(Var)
      IsBlank = True
    Case IsArray(Var)
      If UBound(Var) = 0 Then IsBlank = True
    Case IsNumeric(Var)
      If (Var = 0) Then IsBlank = True
    Case Else
      If Trim(Var) = "" Then IsBlank = True
  End Select
End Function
```



%>

#### 14.用于取代 request.Form,request.QueryString

<%

Function SafePost(objForm)

Dim strContent

strContent = Trim(Request.Form(objForm))

strContent = Replace(strContent,"'", "")

strContent = Replace(strContent,"'", "")

SafePost = strContent

End function

Function SafeGet(objForm)

Dim strContent

strContent = Trim(Request.QueryString(objForm))

strContent = Replace(strContent,"'", "")

strContent = Replace(strContent,"'", "")

SafeGet = strContent

End function

%>

#### 15.打开 Access 数据库

<%

Function DbOpen()

Dim connStr

Set Conn = server.createobject("adodb.connection")

ConnStr="Provider=Microsoft.Jet.OLEDB.4.0;Data Source ="& Server.MapPath(DBPath)

Conn.Open connStr"DS\_min.cn.com"

DBSTATE = 1

End Function

%>

#### 16.关闭数据库

<%

Function Dbclose()

Conn.Close()

Set Conn = Nothing

DBSTATE = 0

End Function

%>





## 17.FSO 读取文件

```
<%  
Function ReadFile(LocalFilePath)  
Dim ObjFile,FSO_Temlet,FSO_Stream,TruePath  
TruePath = Server.MapPath(LocalFilePath)  
Set ObjFile=Server.CreateObject("Scripting.FileSystemObject")  
If ObjFile.FileExists(TruePath) Then  
Set FSO_Temlet = ObjFile.GetFile(TruePath)  
Set FSO_Stream = FSO_Temlet.OpenAsTextStream(1)  
ReadFile = FSO_Stream.ReadAll  
Set FSO_Temlet = Nothing  
Set FSO_Stream = Nothing  
Else  
ReadFile = "FileNotFound"&TruePath  
End If  
Set ObjFile = Nothing  
End Function  
>
```

## 18.中断函数

```
<%  
Function Break(ErrInfo,DbOff,ToErrCenter)  
If DbOff = 1 Then DBClose()  
If ToErrCenter = 1 Then  
Response.Redirect("ShowError.asp?msg="&Server.URLEncode(ErrorArr(0)))  
Response.End()  
Else  
Response.Write "<p align=center>"& ErrInfo &"</p>"  
Response.End()  
End If  
End Function  
>
```



## 19.用 Jmail 组件发送邮件

```
<%  
*****  
'函数名: SendMail  
'作用: 用 Jmail 组件发送邮件  
'参数: MailtoAddress ----收信人地址
```





```
' MailtoName -----收信人姓名
' Subject -----主题
' MailBody -----信件内容
' FromName -----发信人姓名
' MailFrom -----发信人地址
' Priority -----信件优先级
```

```
*****
```

```
function SendMail(MailtoAddress,MailtoName,Subject,MailBody,FromName,MailFrom,Priority)
  on error resume next
  Dim JMail
  Set JMail=Server.CreateObject("JMail.Message")
  if err then
    SendMail= "<br><li>没有安装 JMail 组件</li>"
    err.clear
    exit function
  end if
  JMail.Charset="gb2312" '邮件编码
  JMail.silent=true
  JMail.ContentType = "text/html" '邮件正文格式
  'JMail.ServerAddress=MailServer '用来发送邮件的 SMTP 服务器
  '如果服务器需要 SMTP 身份验证则还需指定以下参数
  JMail.MailServerUserName = MailServerUserName '登录用户名
  JMail.MailServerPassWord = MailServerPassword '登录密码
  JMail.MailDomain = MailDomain '域名（如果用"name@domain.com"这样的用户名登录时，请指明
domain.com
  JMail.AddRecipient MailtoAddress,MailtoName '收信人
  JMail.Subject=Subject '主题
  JMail.HTMLBody=MailBody '邮件正文（HTML 格式）
  JMail.Body=MailBody '邮件正文（纯文本格式）
  JMail.FromName=FromName '发信人姓名
  JMail.From = MailFrom '发信人 Email
  JMail.Priority=Priority '邮件等级，1 为加急，3 为普通，5 为低级
  JMail.Send(MailServer)
  SendMail =JMail.ErrorMessage
  JMail.Close
  Set JMail=nothing
end function
%>
```



## 20.处理含有?和&的网址

```
<%
```

```
*****
```

```
'函数名: JoinChar
```

'作用: 向地址中加入 ? 或 &

'参数: strSql ----网址

'返回值: 加了 ? 或 & 的网址

\*\*\*\*\*

```
function JoinChar(strUrl)
    if strSql="" then
        JoinChar=""
        exit function
    end if
    if InStr(strUrl,"?")<len(strUrl) then
        if InStr(strUrl,"?")>1 then
            if InStr(strUrl,"&")<len(strUrl) then
                JoinChar=strUrl & "&"
            else
                JoinChar=strUrl
            end if
        else
            JoinChar=strUrl & "?"
        end if
    else
        JoinChar=strUrl
    end if
end function
%>
```

## 21.生成静态页面

<%

'=====

'过程名: savestaticpage

'作用: 保存为静态页面

'参数: from——地址, tofile——文件名

'=====

```
sub savestaticpage(from,tofile)
    set fso=Server.CreateObject("Scripting.FileSystemObject")
    PostUrl="http://"& host &&am ... ;ot; & from
    Rvalue=SendToSp(PostUrl)
    Rvalue=Bytes2bStr(Rvalue)
    if Rvalue="" then
        if err then
            WriteErrMsg(err.description)
        end if
    response.End()
end sub
```



```

end if
Set hf = fso.CreateTextFile(tofile, True)
hf.Write Rvalue
hf.Close
set hf=nothing
set fso=nothing
end sub
'读取 URL 接口
Function SendToSp(PostUrl)
    IsSuccess=""
    Set xml = Server.CreateObject("Microsoft.XMLHTTP")
    xml.Open "GET",PostUrl,False
    xml.Send
    'if xml.readystate<>4 then
    ' WriteErrMsg("更新页面失败，可能是服务器故障，请稍后在试!!! ")
    ' SendToSp=""
    ' exit function
    'end if
    IsSuccess= xml.Responsebody
    Set xml = Nothing
    SendToSp = IsSuccess
End Function

```

```

Const adTypeBinary = 1
Const adTypeText = 2

```

```

'转换接口值为字符串
Function Bytes2bStr(vin)
Dim BytesStream,StringReturn

Set BytesStream = Server.CreateObject("ADODB.Stream")
With BytesStream
.Type=adTypeText
.Open
.WriteText vin
.Position = 0
.Charset = "GB2312" )
.Position = 2
StringReturn = .ReadText
.close
End With
Set BytesStream = Nothing
Bytes2bStr = StringReturn
End Function

```



%>

## 22.过滤非法字符

<%

\*\*\*\*\*

'函数名: ReplaceBadChar

'作用: 过滤非法的 SQL 字符

'参数: strChar-----要过滤的字符

'返回值: 过滤后的字符

\*\*\*\*\*

Function Checkstr(Str)

If Isnull(Str) Then

    CheckStr = ""

    Exit Function

End If

Str = Replace(Str,Chr(0),"", 1, -1, 1)

Str = Replace(Str, "''", "&quot;", 1, -1, 1)

Str = Replace(Str,"<","&lt;", 1, -1, 1)

Str = Replace(Str,">","&gt;", 1, -1, 1)

Str = Replace(Str, "script", "&#115;cript", 1, -1, 0)

Str = Replace(Str, "SCRIPT", "&#083;CRIPT", 1, -1, 0)

Str = Replace(Str, "Script", "&#083;cript", 1, -1, 0)

Str = Replace(Str, "script", "&#083;cript", 1, -1, 1)

Str = Replace(Str, "object", "&#111;bject", 1, -1, 0)

Str = Replace(Str, "OBJECT", "&#079;BJECT", 1, -1, 0)

Str = Replace(Str, "Object", "&#079;bject", 1, -1, 0)

Str = Replace(Str, "object", "&#079;bject", 1, -1, 1)

Str = Replace(Str, "applet", "&#097;pplet", 1, -1, 0)

Str = Replace(Str, "APPLET", "&#065;PPLET", 1, -1, 0)

Str = Replace(Str, "Applet", "&#065;pplet", 1, -1, 0)

Str = Replace(Str, "applet", "&#065;pplet", 1, -1, 1)

Str = Replace(Str, "[", "&#091;")

Str = Replace(Str, "]", "&#093;")

Str = Replace(Str, "''", "", 1, -1, 1)

Str = Replace(Str, "=", "&#061;", 1, -1, 1)

Str = Replace(Str, "''", "''", 1, -1, 1)

Str = Replace(Str, "select", "select", 1, -1, 1)

Str = Replace(Str, "execute", "&#101;xecute", 1, -1, 1)

Str = Replace(Str, "exec", "&#101;xec", 1, -1, 1)

Str = Replace(Str, "join", "join", 1, -1, 1)

Str = Replace(Str, "union", "union", 1, -1, 1)



```
Str = Replace(Str, "where", "where", 1, -1, 1)
Str = Replace(Str, "insert", "insert", 1, -1, 1)
Str = Replace(Str, "delete", "delete", 1, -1, 1)
Str = Replace(Str, "update", "update", 1, -1, 1)
Str = Replace(Str, "like", "like", 1, -1, 1)
Str = Replace(Str, "drop", "drop", 1, -1, 1)
Str = Replace(Str, "create", "create", 1, -1, 1)
Str = Replace(Str, "rename", "rename", 1, -1, 1)
Str = Replace(Str, "count", "co&#117;nt", 1, -1, 1)
Str = Replace(Str, "chr", "c&#104;r", 1, -1, 1)
Str = Replace(Str, "mid", "m&#105;d", 1, -1, 1)
Str = Replace(Str, "truncate", "trunc&#097;te", 1, -1, 1)
Str = Replace(Str, "nchar", "nch&#097;r", 1, -1, 1)
Str = Replace(Str, "char", "ch&#097;r", 1, -1, 1)
Str = Replace(Str, "alter", "alter", 1, -1, 1)
Str = Replace(Str, "cast", "cast", 1, -1, 1)
Str = Replace(Str, "exists", "e&#120;ists", 1, -1, 1)
Str = Replace(Str,Chr(13),"<br>", 1, -1, 1)
CheckStr = Replace(Str,""," ", 1, -1, 1)
end function
%>
```

[color=Red]23 纯 ASP 代码生成图表函数[/color]

<%

function table2(total,table\_x,table\_y,all\_width,all\_height,line\_no)

'参数含义(传递的数组,横坐标,纵坐标,图表的宽度,图表的高度,折线条数)

'纯 ASP 代码生成图表函数 2——折线图

' 作者 : 龚 鸣 (Passwordgm) QQ:25968152 MSN:passwordgm@sina.com

Email:passwordgm@sina.com

'本人非常愿意和 ASP,VML,FLASH 的爱好者在 HTTP://topclouds.126.com 进行交流和探讨

'版本 1.0 最后修改日期 2003-8-11

'非常感谢您使用这个函数,请您使用和转载时保留版权信息,这是对作者工作的最好的尊重。

line\_color="#69f"

left\_width=70

total\_no=ubound(total,1)

temp1=0

for i=1 to total\_no

for j=1 to line\_no

if temp1<total(i,j) then temp1=total(i,j)

next

next

```

temp1=int(temp1)
if temp1>9 then
temp2=mid(cstr(temp1),2,1)
if temp2>4 then
temp3=(int(temp1/(10^(len(cstr(temp1))-1)))+1)*10^(len(cstr(temp1))-1)
else
temp3=(int(temp1/(10^(len(cstr(temp1))-1)))+0.5)*10^(len(cstr(temp1))-1)
end if
else
if temp1>4 then temp3=10 else temp3=5
end if
temp4=temp3
response.write "<v:rect id='_x0000_s1027' alt="
style='position:absolute;left:"&table_x+left_width&"px;top:"&table_y&"px;

width:"&all_width&"px;height:"&all_height&"px;z-index:-1' fillcolor='#9cf' stroked='f'><v:fill
rotate='t' angle='-45' focus='100%' type='gradient'/></v:rect>"
for i=0 to all_height-1 step all_height/5
response.write "<v:line id='_x0000_s1027' alt="
style='position:absolute;left:0;text-align:left;top:0;flip:y;z-index:-1'
from="&table_x+left_width+length&"px,"&table_y+all_height-length-i&"px'
to="&table_x+all_width+left_width&"px,"&table_y+all_height-length-i&"px'
strokecolor="&line_color&""/>"
response.write "<v:line id='_x0000_s1027' alt="
style='position:absolute;left:0;text-align:left;top:0;flip:y;z-index:-1'
from="&table_x+(left_width-15)&"px,"&table_y+i&"px'
to="&table_x+left_width&"px,"&table_y+i&"px"/>"
response.write ""
response.write "<v:shape id='_x0000_s1025' type='#_x0000_t202' alt="
style='position:absolute;left:"&table_x&"px;top:"&table_y+i&"px;

width:"&left_width&"px;height:18px;z-index:1'>"
response.write "<v:textbox inset='0px,0px,0px,0px'><table cellpadding='0'
width='100%' height='100%'><tr><td
align='right'>"&temp4&"</td></tr></table></v:textbox></v:shape>"
temp4=temp4-temp3/5
next
response.write "<v:line id='_x0000_s1027' alt="
style='position:absolute;left:0;text-align:left;top:0;flip:y;z-index:-1'
from="&table_x+left_width&"px,"&table_y+all_height&"px'
to="&table_x+all_width+left_width&"px,"&table_y+all_height&"px"/>"
response.write "<v:line id='_x0000_s1027' alt="
style='position:absolute;left:0;text-align:left;top:0;flip:y;z-index:-1'
from="&table_x+left_width&"px,"&table_y&"px'

```

```
to=""&table_x+left_width&"px,"&table_y+all_height&"px"/>"
```

```
dim line_code
redim line_code(line_no,5)
for i=1 to line_no
line_temp=split(total(0,i),",")
line_code(i,1)=line_temp(0)
line_code(i,2)=line_temp(1)
line_code(i,3)=line_temp(2)
line_code(i,4)=line_temp(3)
line_code(i,5)=line_temp(4)
next
for j=1 to line_no
for i=1 to total_no-1
x1=table_x+left_width+all_width*(i-1)/total_no
y1=table_y+(temp3-total(i,j))*(all_height/temp3)
x2=table_x+left_width+all_width*i/total_no
y2=table_y+(temp3-total(i+1,j))*(all_height/temp3)
response.write "<v:line id=""_x0000_s1025"" alt=""
style='position:absolute;left:0;text-align:left;top:0;z-index:1' from=""&x1&"px,"&y1&"px""
to=""&x2&"px,"&y2&"px"" coordsize=""21600,21600"" strokecolor=""&line_code(j,1)&""
strokeweight=""&line_code(j,2)&"">"
select case line_code(j,3)
case 1
case 2
response.write "<v:stroke dashstyle='1 1'/>"
case 3
response.write "<v:stroke dashstyle='dash'/>"
case 4
response.write "<v:stroke dashstyle='dashDot'/>"
case 5
response.write "<v:stroke dashstyle='longDash'/>"
case 6
response.write "<v:stroke dashstyle='longDashDot'/>"
case 7
response.write "<v:stroke dashstyle='longDashDotDot'/>"
case else
end select
response.write "</v:line>"&CHR(13)
select case line_code(j,4)
case 1
case 2
response.write "<v:rect id=""_x0000_s1027""
style='position:absolute;left:"&x1-2&"px;top:"&y1-2&"px;width:4px;height:4px; z-index:2'
```



```

fillcolor=""&line_code(j,1)&"" strokecolor=""&line_code(j,1)&""/>"&CHR(13)
  case 3
    response.write          "<v:oval          id=""_x0000_s1026""
style='position:absolute;left:"&x1-2&"px;top:"&y1-2&"px;width:4px;height:4px;z-index:1'
fillcolor=""&line_code(j,1)&"" strokecolor=""&line_code(j,1)&""/>"&CHR(13)
    end select
next
  select case line_code(j,4)
  case 1
  case 2
    response.write          "<v:rect          id=""_x0000_s1027""
style='position:absolute;left:"&x2-2&"px;top:"&y2-2&"px;width:4px;height:4px;      z-index:2'
fillcolor=""&line_code(j,1)&"" strokecolor=""&line_code(j,1)&""/>"&CHR(13)
    case 3
    response.write          "<v:oval          id=""_x0000_s1026""
style='position:absolute;left:"&x2-2&"px;top:"&y2-2&"px;width:4px;height:4px;z-index:1'
fillcolor=""&line_code(j,1)&"" strokecolor=""&line_code(j,1)&""/>"&CHR(13)
    end select
next

for i=1 to total_no
response.write          "<v:line          id='_x0000_s1027'          alt=""
style='position:absolute;left:0;text-align:left;top:0;flip:y;z-index:-1'
from=""&table_x+left_width+all_width*(i-1)/total_no&"px,"&table_y+all_height&"px'
to=""&table_x+left_width+all_width*(i-1)/total_no&"px,"&table_y+all_height+15&"px"/>"
response.write ""
response.write          "<v:shape          id='_x0000_s1025'          type='#_x0000_t202'          alt=""
style='position:absolute;left:"&table_x+left_width+all_width*(i-1)/total_no&"px;top:"&table_y+a
ll_height&"px;width:"&all_width/total_no&"px;height:18px;z-index:1'>"
response.write          "<v:textbox inset='0px,0px,0px,0px'><table cellpadding='0'
width='100%'          height='100%'><tr><td
align='left'>"&total(i,0)&"</td></tr></table></v:textbox></v:shape>"
next

tb_height=30
response.write          "<v:rect          id='_x0000_s1025'
style='position:absolute;left:"&table_x+all_width+20&"px;top:"&table_y&"px;

width:100px;height:"&line_no*tb_height+20&"px;z-index:1'>"
for i=1 to line_no
response.write          "<v:shape          id='_x0000_s1025'          type='#_x0000_t202'          alt=""
style='position:absolute;left:"&table_x+all_width+25&"px;top:"&table_y+10+(i-1)*tb_height&"p
x;width:60px;height:"&tb_height&"px;z-index:1'>"
response.write          "<v:textbox inset='0px,0px,0px,0px'><table cellpadding='0'

```



```

width='100%'
height='100%'><tr><td
align='left'>&line_code(i,5)&"</td></tr></table></v:textbox></v:shape>"
response.write
"<v:rect
id='_x0000_s1040'
alt="
style='position:absolute;left:"&table_x+all_width+80&"px;top:"&table_y+10+(i-1)*tb_height+4
&"px;width:30px;height:20px;z-index:1'
fillcolor=""&line_code(i,1)&"><v:fill
color2=""&line_code(i,1)&" rotate='t' focus='100%' type='gradient'/></v:rect>"
next

end function
%>

```



```

<%
function table3(total,table_x,table_y,all_width,all_height,table_type)
'参数含义(传递的数组, 横坐标, 纵坐标, 图表的宽度, 图表的高度,图表的类型)
'纯 ASP 代码生成图表函数 3——饼图
' 作者 : 龚 鸣 (Passwordgm) QQ:25968152 MSN:passwordgm@sina.com
Email:passwordgm@sina.com
'本人非常愿意和 ASP,VML,FLASH 的爱好者在 HTTP://topclouds.126.com 进行交流和探讨
'版本 1.0 最后修改日期 2003-8-11
'非常感谢您使用这个函数, 请您使用和转载时保留版权信息, 这是对作者工作的最好的尊重。

```

```

tb_height=30

dim tb_color(7,2)
tb_color(1,1)="#d1ffd1"
tb_color(2,1)="#ffb3bb"
tb_color(3,1)="#ffe3bb"
tb_color(4,1)="#cff4f3"
tb_color(5,1)="#d9d9e5"
tb_color(6,1)="#ffc7ab"
tb_color(7,1)="#ecffb7"

tb_color(1,2)="#00ff00"
tb_color(2,2)="#ff0000"
tb_color(3,2)="#ff9900"
tb_color(4,2)="#33cccc"
tb_color(5,2)="#666699"
tb_color(6,2)="#993300"
tb_color(7,2)="#99cc00"

```

```

total_no=ubound(total,1)

```

```

totalpie=0
for i=1 to total_no
totalpie=totalpie+total(i,1)
next

```



```

PreAngle=0
for i=1 to total_no
response.write          "<v:shape          id='_x0000_s1025'          alt="
style='position:absolute;left:"&table_x&"px;top:"&table_y&"px;width:"&all_width&"px;height:"
&all_height&"px;z-index:1'          coordsize='1500,1400'          o:spt='100'          adj='0,0'
path='m750,700ae750,700,750,700,"&int(23592960*PreAngle)&',"&int(23592960*total(i,1)/totalpie)&"xe'
          fillcolor=""&tb_color(i,1)&"          strokecolor='#FFFFFF'><v:fill
color2=""&tb_color(i,2)&"          rotate='t'          focus='100%'          type='gradient'><v:stroke
jointstyle='round'><v:formulas/><v:path o:connecttype='segments'></v:shape>"&Chr(13)
PreAngle=PreAngle+total(i,1)/totalpie
next

```

```

if table_type="A" then
response.write          "<v:rect          id='_x0000_s1025'
style='position:absolute;left:"&table_x+all_width+20&"px;top:"&table_y+20&"px;width:100px;h
eight:"&total_no*tb_height+20&"px;z-index:1'>"
for i=1 to total_no
response.write          "<v:shape          id='_x0000_s1025'          type='#_x0000_t202'          alt="
style='position:absolute;left:"&table_x+all_width+25&"px;top:"&table_y+30+(i-1)*tb_height&"p
x;width:60px;height:"&tb_height&"px;z-index:1'>"
response.write          "<v:textbox inset='0px,0px,0px,0px'><table cellpadding='0'
width='100%'          height='100%'><tr><td
align='left'>"&total(i,0)&"</td></tr></table></v:textbox></v:shape>"
response.write          "<v:rect          id='_x0000_s1040'          alt="
style='position:absolute;left:"&table_x+all_width+80&"px;top:"&table_y+30+(i-1)*tb_height+3
&"px;width:30px;height:20px;z-index:1'          fillcolor=""&tb_color(i,1)&"><v:fill
color2=""&tb_color(i,2)&"          rotate='t' focus='100%' type='gradient'></v:rect>"
'显示比例数
' response.write          "<v:shape          id='_x0000_s1025'          type='#_x0000_t202'          alt="
style='position:absolute;left:"&table_x+all_width+110&"px;top:"&table_y+30+(i-1)*tb_height&"
px;width:60px;height:"&tb_height&"px;z-index:1'>"
' response.write          "<v:textbox inset='0px,0px,0px,0px'><table cellpadding='0'
width='100%'          height='100%'><tr><td
align='left'>"&formatnumber(total(i,1)*100/totalpie,2,-1)&"%</td></tr></table></v:textbox></v:
shape>"
next
end if

```

```

if table_type="B" then

```

```

pie=3.14159265358979
TempPie=0
for i=1 to total_no
TempAngle=pie*2*(total(i,1)/(TotalPie*2)+TempPie)
x1=table_x+all_width/2+cos(TempAngle)*all_width*3/8
y1=table_y+all_height/2-sin(TempAngle)*all_height*3/8
x2=table_x+all_width/2+cos(TempAngle)*all_width*3/4
y2=table_y+all_height/2-sin(TempAngle)*all_height*3/4
if x2>table_x+all_width/2 then
    x3=x2+20
    x4=x3
else
    x3=x2-20
    x4=x3-100
end if
response.write          "<v:oval          id='_x0000_s1027'
style='position:absolute;left:"&x1-2&"px;top:"&y1-2&"px;width:4px;height:4px;          z-index:2'
fillcolor=#111111' strokecolor=#111111'/>"&CHR(13)
response.write          "<v:line          id='_x0000_s1025'          alt="
style='position:absolute;left:0;text-align:left;top:0;z-index:1'          from="&x1&"px,"&y1&"px'
to="&x2&"px,"&y2&"px'          coordsize='21600,21600'          strokecolor=#111111'
strokeweight='1px'></v:line>"
response.write          "<v:line          id='_x0000_s1025'          alt="
style='position:absolute;left:0;text-align:left;top:0;z-index:1'          from="&x2&"px,"&y2&"px'
to="&x3&"px,"&y2&"px'          coordsize='21600,21600'          strokecolor=#111111'
strokeweight='1px'></v:line>"
response.write          "<v:shape          id='_x0000_s1025'          type=#_x0000_t202'          alt="
style='position:absolute;left:"&x4&"px;top:"&y2-10&"px;width:100px;height:20px;z-index:1">"
response.write          "<v:textbox          inset='0px,0px,0px,0px'><table          cellspacing='3'          cellpadding='0'
width='100%'          height='100%'><tr><td          align='left'>"&total(i,0)&
"&formatnumber(total(i,1)*100/totalpie,2,-1)&"%</td></tr></table></v:textbox></v:shape>"
TempPie=TempPie+total(i,1)/TotalPie
next
end if

end function
%>

```

[color=Red]24 使用 ASP 在 IIS 创建 WEB 站点的函数[/color]  
<%

=====

'函数介绍：创建 WebSite

'本函数使用 ADSI，需要 Administrators 组用户权限

' 函 数 名 称 :  
CreateWebSite(Computer,IPAddr,PortNum,HostName,WebSiteDirectory,LogDirectory,WebSiteInfo,GuestUserName,GuestUserPass,StartOrStop)

'用法：CreateWebSite 计算机名(一般为 LocalHost 或 127.0.0.1),站点 IP 地址,端口号,主机名,站点根目录,,LOG 文件的目录站点说明,网站访问时所使用的帐号,网站访问时所用帐号的口令,是否启动站点

' 例 : CreateWebSite  
"LocalHost","127.0.0.123","80","www.test.net","E:\UserData\UserNum001","E:\UserData\UserNum001\LogFiles","wwwtest.net","IUSR\_Num001\_test.net","abc888",True

=====

Function

CreateWebSite(Computer,IPAddr,PortNum,HostName,WebSiteDirectory,LogDirectory,WebSiteInfo,GuestUserName,GuestUserPass,StartOrStop)

Dim w3svc, WebServer, NewWebServer, NewDir

Dim Bindings, BindingString, NewBindings, SiteNum, SiteObj, bDone

On Error Resume Next

Err.Clear

'检测是否能够加载 W3SVC 服务（即 WEB 服务）

Set w3svc = GetObject("IIS://" & Computer & "/w3svc")

If Err.Number <> 0 Then '显示错误提示

    response.write "无法打开: "&"IIS://" & Computer & "/w3svc"

    response.end

End If

'检测是否有设定相同 IP 地址、端口及主机名的站点存在

BindingString = IPAddr & ":" & PortNum & ":" & HostName

For Each WebServer in w3svc

    If WebServer.Class = "IIsWebServer" Then

        Bindings = WebServer.ServerBindings

        If BindingString = Bindings(0) Then

            response.write "IP 地址冲突:" & IPAddr & ",请检测 IP 地址! ."

            Exit Function

        End If

    End If

Next

'确定一个不存在的站点编号做为新建站点编号，系统默认 WebSite 站点编号为 1，因此从 2 开始

SiteNum=2

bDone = False

While (Not bDone)



```

Err.Clear
Set SiteObj = GetObject("IIS://" & Computer & "/w3svc/" & SiteNum) '加载指定站点
If (Err.Number = 0) Then
    'response.write " Step_1 站点"&SiteNum&"存在"
    SiteNum = SiteNum + 1
Else
    'response.write " Step_1 站点"&SiteNum&"不存在"
    Err.Clear
    Set NewWebServer = w3svc.Create("IIsWebServer", SiteNum) '创建指定站点
    If (Err.Number <> 0) Then
        'response.write " Step_2 站点"&SiteNum&"创建失败"
        SiteNum = SiteNum + 1
    Else
        'response.write " Step_2 站点"&SiteNum&"创建成功"
        bDone = True
    End If
End If
If (SiteNum > 50) Then '服务器最大创建站点数
    response.write "超出服务器最大创建站点数，正在创建的站点的序号为： "&SiteNum&". "
    response.end
End If
Wend

```

```

'进行站点基本配置
NewBindings = Array(0)
NewBindings(0) = BindingString
NewWebServer.ServerBindings = NewBindings
NewWebServer.ServerComment = WebSiteInfo
NewWebServer.AnonymousUserName = GuestUserName
NewWebServer.AnonymousUserPass = GuestUserPass
NewWebServer.KeyType = "IIsWebServer"
NewWebServer.FrontPageWeb = True
NewWebServer.EnableDefaultDoc = True
NewWebServer.DefaultDoc = "Default.htm, Default.asp, Index.htm, Index.asp"
NewWebServer.LogFileDirectory = LogDirectory
NewWebServer.SetInfo
Set NewDir = NewWebServer.Create("IIsWebVirtualDir", "ROOT")
NewDir.Path = WebSiteDirectory
NewDir.AccessRead = true
NewDir.AppFriendlyName = "应用程序" & WebSiteInfo
NewDir.AppCreate True
NewDir.AccessScript = True
Err.Clear

```



```

NewDir.SetInfo
If (Err.Number <> 0) Then
    response.write "主目录创建时出错."
    response.end
End If
If StartOrStop = True Then
    Err.Clear
    Set NewWebServer = GetObject("IIS://" & Computer & "/w3svc/" & SiteNum)
    NewWebServer.Start
    If Err.Number <> 0 Then
        response.write "启动站点时出错!"
        response.end
        Err.Clear
    End If
End If
response.write "站点创建成功， 站点编号为： "& SiteNum &" ， 域名为： "& HostName
End Function

```

使用 ASP 启动/停止指定 WEB 站点

---

```

'函数介绍： 使用 ASP 启动/停止指定 WEB 站点
'本函数使用 ADSI， 需要 Administrators 组用户权限
'函数名称： AdminWebSite(Computer,WebSiteNum,DoWhat)
'用法： AdminWebSite(计算机名称,站点编号,启动/停止)
'例： 启动 127.0.0.1 计算机上站点编号为 1 的站点
'AdminWebSite "127.0.0.1","1",1
'例： 停止 127.0.0.1 计算机上站点编号为 1 的站点
'AdminWebSite "127.0.0.1","1",0

```

---

```

Function AdminWebSite(Computer,WebSiteNum,DoWhat)
On Error Resume Next
Set objServer = GetObject("IIS://" & Computer & "/W3SVC/" & WebSiteNum)
If Err.Number <> 0 Then
    Response.Write Now & ". 错误码: " & Hex(Err)& " - " & "无法开启指定站点<br>"
End If
if Dowhat=1 then
'使用 Start 启动站点
    objServer.Start
    If Err.Number <> 0 Then
        Response.Write "无法启动指定 Web 站点<br>"
    else
        Response.Write "已经启动指定 Web 站点<br>"
    End If
elseif DoWhat=0 then
'使用 Stop 停止站点

```



```
objServer.Stop
If Err.Number <> 0 Then
    Response.Write "无法停止指定 Web 站点<br>"
else
    Response.Write "已经停止指定 Web 站点<br>"
End If
end if
End Function
```

使用 ASP 列出服务器 WEB 站点信息

```
'=====
'函数介绍：列出当前服务器 WEB 站点信息
'本函数使用 ADSI，需要 Administrators 组用户权限
'函数名称：ListWebSite (Computer,Num)
'用法：ListWebSite (计算机名称,显示站点数量)
'例：显示 127.0.0.1 计算机上 1000 个站点信息
'ListWebSite "127.0.0.1","1000"
'=====
```

```
Function ListWebSite(Computer,Num)
On Error Resume Next
Set SiteObj = GetObject("IIS://" & Computer & "/w3svc/" & i)
for i=0 to Num
    Err.Clear
    if Err.Number=0 then
        response.write "<p><b>以下显示为计算机： "& Computer & "上所有站点信息</b></p>"
        ShowWebSite = SiteObj.Get("ServerBindings") '获得站点 IP 地址:端口:主机头
        Info=split(ShowWebSite(0),":")
        response.write "站点编号： "& i & "<br>"
        response.write "站点 IP 地址： "& Info(0) & "<br>"
        response.write "站点端口： "& Info(1) & "<br>"
        response.write "站点主机头： "& Info(2) & "<br><br>"
    end if
end for
next
set SiteObj=nothing
End Function
```

使用 ASP 删除指定 IIS 站点

```
'=====
'函数介绍：删除指定 IIS 站点
'本函数使用 ADSI，需要 Administrators 组用户权限
'函数名称：DelWebSite (Computer,SiteNum)
'用法：DelWebSite 计算机名，站点编号
'例：DelWebSite "127.0.0.1","2"
'=====
```

```
Function DelWebSite(Computer,SiteNum)
Set W3SVC = GetObject("IIS://" & Computer & "/w3svc")
```

```
W3SVC.delete "IIsWebServer",SiteNum
```

```
response.write "删除成功! "
```

```
End Function
```

```
通过 ASP 管理 NT 帐号
```

---

```
'函数介绍: 通过 ASP 管理 NT 帐号
```

```
'本函数使用 ADSI, 需要 Administrators 组用户权限
```

---

```
'添加用户
```

```
'函数用法: AddUser(Computer,UserName,PassWord,FullName,Info)
```

```
'参数: 计算机名,帐号名称,帐号密码,帐号全名,帐号说明
```

```
'例: AddUser "127.0.0.1","Test","Test","测试管理员帐号","本帐号通过 ASP 添加"
```

```
'修改指定用户基本信息
```

```
'函数用法: EditUser(Computer,UserName,OldPassWord,PassWord,FullName,Info)
```

```
'参数: 计算机名,帐号名称,帐号密码,帐号全名,帐号说明
```

```
'例: EditUser "127.0.0.1","Test","Test2","测试管理员帐号修改","本帐号通过 ASP 修改过"
```

```
'删除指定用户
```

```
'函数用法: DelUser(Computer,UserName)
```

```
'参数: 计算机名,用户名'
```

```
'例: DelUser "127.0.0.1","Test"
```

---

```
Function AddUser(Computer,UserName,PassWord,FullName,Info)
```

```
'执行创建帐号命令
```

```
Set ComputerObj = GetObject("WinNT://" & Computer)
```

```
Set NewUser = ComputerObj.Create( "User" , UserName )
```

```
NewUser.SetInfo
```

```
'进行帐号设置
```

```
NewUser.SetPassword ( PassWord ) '帐号密码
```

```
NewUser.FullName = FullName '帐号全名
```

```
NewUser.Description = Info '帐号说明
```

```
NewUser.UserFlags = &H10000 ' &H20000(使用者下次登入时须变更密码) &H0040(使用者不得变更密码) &H10000(密码永久正确) &H0002(帐户暂时停用)
```

```
NewUser.SetInfo
```

```
response.write "帐号"&UserName&"创建成功! "
```

```
Set ComputerObj=nothing
```

```
End Function
```

```
Function EditUser(Computer,UserName,OldPassWord,PassWord,FullName,Info)
```

```
'读取用户信息
```

```
Set ChangeUserObj = GetObject("WinNT://" & Computer & "/" & UserName & ",User")
```

```
'修改帐号密码
```

```
if PassWord <> "" then
```

```
    ChangeUserObj.SetPassword PassWord
```



```

    response.write "帐号密码修改成功! <br>"
end if
'修改帐号全名
if FullName<>"" then
    UserFullName = ChangeUserObj.get("FullName")
    ChangeUserObj.FullName = FullName
    ChangeUserObj.SetInfo
    response.write "帐号全名修改成功! <br>"
end if
'修改帐号说明
if Info<>"" then
    UserFullName = ChangeUserObj.get("Description")
    ChangeUserObj.Description = Info
    ChangeUserObj.SetInfo
    response.write "帐号说明修改成功! <br>"
end if
Set ChangeUserObj=nothing
End Function

```



```

Function DelUser(Computer,UserName)
Set DelUserObj = GetObject("WinNT://"&Computer&"/"&UserName)
If Err = &H800401E4 Then
    Response.Write "用户"&UserName&"不存在"
    Response.End
End If
Set DelObj = GetObject(DelUserObj.Parent)
DelObj.Delete "User", DelUserObj.Name
Set DelUserObj = Nothing
Set DelObj = Nothing
Response.Write "删除成功"
End Function

```

使用 ASP 控制指定站点解析脚本语言函数

```

Function AdminAegis(Computer,SiteNum)
Set IISWebServiceObj = GetObject("IIS://"&Computer&"/W3SVC/"&SiteNum)
dim Aegis(1)
Aegis(0)="asp,C:\WINNT\system32\inetsrv\asp.dll,5,GET,HEAD,POST,TRACE"
'Aegis(1)="aspx,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet_isapi.dll,1,GET,HEAD
,POST,DEBUG"
'解析其它文件请同样使用 Aegis(Num)="这种格式，记得要将 dim Aegis(Num)定义
'.htw,C:\WINNT\system32\webhits.dll,3,GET,HEAD,POST
'.ida,C:\WINNT\system32\idq.dll,7,GET,HEAD,POST
'.idq,C:\WINNT\system32\idq.dll,7,GET,HEAD,POST
'.asp,C:\WINNT\system32\inetsrv\asp.dll,5,GET,HEAD,POST,TRACE
'.cer,C:\WINNT\system32\inetsrv\asp.dll,5,GET,HEAD,POST,TRACE

```

'cdx,C:\WINNT\system32\inetsrv\asp.dll,5,GET,HEAD,POST,TRACE  
'asa,C:\WINNT\system32\inetsrv\asp.dll,5,GET,HEAD,POST,TRACE  
'idc,C:\WINNT\system32\inetsrv\httpodbc.dll,5,GET,POST<br>  
'shtm C:\WINNT\system32\inetsrv\ssinc.dll,5,GET,POST<br>  
'shtml C:\WINNT\system32\inetsrv\ssinc.dll,5,GET,POST<br>  
'stm C:\WINNT\system32\inetsrv\ssinc.dll,5,GET,POST<br>  
'asax  
C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POST,DEBUG  
'ascx,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POST,DE  
BUG  
'ashx,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,1,GET,HEAD,POST,DE  
BUG  
'asmx,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,1,GET,HEAD,POST,D  
EBUG  
'aspx,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,1,GET,HEAD,POST,DE  
BUG  
'axd,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,1,GET,HEAD,POST,DE  
BUG  
'vsdisco,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,1,GET,HEAD,POST,  
DEBUG  
'rem,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,1,GET,HEAD,POST,DE  
BUG  
'soap,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,1,GET,HEAD,POST,DE  
BUG  
'config,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POST,D  
EBUG  
'cs,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POST,DEB  
UG  
'csproj,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POST,D  
EBUG  
'vb,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POST,DEB  
UG  
'vbproj,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POST,D  
EBUG  
'webinfo,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POST,  
DEBUG  
'licx,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POST,DE  
BUG  
'resx,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POST,DE  
BUG  
'resources,C:\WINNT\Microsoft.NET\Framework\v1.1.4322\aspnet\_isapi.dll,5,GET,HEAD,POS  
T,DEBUG  
IlsWebServiceObj.ScriptMaps=Aegis  
IlsWebServiceObj.SetInfo





```
dim guest
if isnull(str) or str="" then
    htmlOut=str
    exit function
end if
guest=str
guest=Replace(Guest," "," ")
guest=Replace(Guest," ","`nbsp;")

Guest=server.htmlencode(Guest)
guest=Replace(Guest,"`nbsp;"," ")
guest=Replace(Guest,vbCrLf,"<BR>")
HtmlOut=guest
end function

%>
```

[color=Red]26.从数据库中提取内容生成下拉菜单[/color]

```
<%
public function OutOption(conn,tabel,style,value)
'从数据库中提取内容生成下拉菜单
'conn 为数据库联接 table 为表名 style 下接菜单样式
    dim re,sql,selected
    set re=server.CreateObject("ADODB.RECORDSET")
    sql = "SELECT * FROM " & tabel & " ORDER BY value"
    re.Open sql,conn
    Response.Write ("<select " & style & ">" & vbCrLf)
    while re.EOF<>true
        if trim(re("value"))=trim(value) then
            selected=" selected "
        else
            selected=" "
        end if
        response.write( vbTab & "<option" & selected & "value=""" & re("value") & """">" &
re("text") & "</option>" & vbCrLf)
        re.MoveNext
    wend
    Response.Write ("</select>" & vbCrLf)
    set re=nothing
end function
```

%>

[color=Red]27.时间格式化函数[/color]

<%

Public Function FormatDT(dt, style)

'style=0 2000-10-10 下午 12:17:45

'style=1 2000-10-10 23:17:45

'style=2 2000-10-10 23:45

'style=3 00-10-10 23:45

'style=4 10-10 23:45

'style=5 2000-10-10

'style=6 00-10-10

'style=7 10-10

Dim nowdate, y, m, d, h, i, s, t, APM, hAPM

nowdate = dt

y = Year(nowdate)

m = Month(nowdate)

d = Day(nowdate)

h = Hour(nowdate)

i = Minute(nowdate)

s = Second(nowdate)

If h > 12 Then

APM = "下午 "

hAPM = CStr(CInt(h) Mod 12)

Else

APM = "上午 "

hAPM = h

End If

Select Case style

Case 0

t = y & "-" & m & "-" & d & " " & APM & hAPM & ":" & i & ":" & s

Case 1

t = y & "-" & m & "-" & d & " " & h & ":" & i & ":" & s

Case 2

t = y & "-" & m & "-" & d & " " & h & ":" & i

Case 3

t = Right(y, 2) & "-" & m & "-" & d & " " & h & ":" & i

Case 4

t = m & "-" & d & " " & h & ":" & i

Case 5

t = y & "-" & m & "-" & d



Case 6

t = Right(y, 2) & "-" & m & "-" & d

Case 7

t = m & "-" & d

End Select

FormatDT = t

End Function

%>

